



TBP Converting, Inc.
Cactus N2230 PDS



Product Information

Cactus® Double Coated Foam Tape N2230 is an acrylic solvent based adhesive tape that offers high shear strength and tack for secure bonding applications. Made with an easy removable liner and is reinforced with white 3 PCF cross-linked polyethylene foam tape for excellent adhesion to irregular and contour surfaces.

Composition & Physical Properties

Adhesive System	: Solvent Acrylic	Tape Thickness	: 1/8" (3.0 ± 0.2 mm)
Carrier	: Polyethylene Foam	Tack	: J. Dow No. 20
Foam Density	: 3 PCF	Peel Adhesion	: PSTC-3 105.8 oz/in (3.0 ± 0.1 kg/25mm)
Liner Material	: Glassine Paper	Shear Strength	: Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0 kg/25mm x 25mm) bonding 2 stainless steel plates at 77°F (25°C)
Liner Thickness	: 3 mil	Normal Tensile Strength	: 528 oz / inch (15kg / 25mm x 25mm)
Liner Density	: #60 (90 g/m ²)	Service Temperature	: -4°F ~ 176°F (-20°C ~ 80°C)
Liner Color	: White	Tape Color	: White

Applications

- Mounting and joining nameplates, signs, plaques, plastic hooks, etc.
- Excellent for long-term mounting of mirror trims.
- Ideal for general purpose indoor and outdoor mounting and joining applications.
- For permanent bonding and repair of metal or plastic articles, e.g. houseware, kitchenware, bathroom accessories, etc.

Disclaimer and Limitation of Liability

In no event shall V. Himark USA and its employees be liable for any indirect, special, incidental or consequential damage resulting from the use of this product. Therefore, it is strongly recommended that the user performs a test application first to determine the suitability of this product for the intended method of application.