



TBP Converting, Inc.
3M Contractor Grade Duct Tape 3979

April, 2014

3M™ Contractor Grade Duct Tape 3979

Product Description

3M™ Contractor Grade Duct Tape 3979 is a utility grade, conformable cloth duct tape made with polyethylene film over cloth scrim and synthetic rubber adhesive. A good choice for protecting, bundling, attaching, poly hanging, holding, and marking.



Product Features

- Aggressive synthetic rubber adhesive provides instant adhesion to a wide variety of surfaces, including concrete, wood, and metal.
- Woven cloth scrim tears straight in both directions.
- Tightly woven scrim for high tensile strength, which is ideal for bundling wire, pipe, and other materials.
- Adhesive works great for masking against coatings.

3M™ Contractor Grade Duct Tape 3979

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Property	Values		Method
Color	Silver		
Total Tape Thickness	0.31 mm	7.9 mil	ASTM D3652
Backing	Polyethylene film over cloth scrim		
Adhesive	Synthetic rubber		

Typical Performance Characteristics

Property	Values		Method	Substrate
Peel Adhesion	7.4 N/cm	68 oz/in	ASTM D3330	Stainless Steel
Tensile Strength	56 N/cm	512 oz/in	ASTM D3759	
Elongation at Break	26 %		ASTM D3759	
Temperature Use Range	Up to 93 °C	Up to 200 °F		

Available Sizes

Property	Values	
Standard Roll Length	54.8 m	60 yd
Standard Width	48, 72 mm	1.88, 2.83 in

3M™ Contractor Grade Duct Tape 3979

Handling/Application Information

Application Ideas

- Hanging poly-drapes
- Bundling, attaching, marking, identifying
- Trip hazard mitigation
- Wire pulling
- Masking coatings

Storage and Shelf Life

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton. To obtain best performance, use this product within 18 months from date of manufacture.

3M™ Contractor Grade Duct Tape 3979

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Trademarks

3M is a trademark of 3M Company.

3M™ Contractor Grade Duct Tape 3979

References

Safety Data Sheet (SDS)

https://www.3m.com/3M/en_US/company-us/SDS-search/results/?gsaAction=msdsSRA&msdsLocale=en_US&co=ptn&q=3979

ISO Statement

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.