



TBP Converting, Inc.
TESA 4334 PDS

tesa® 4334 Precision Mask®

High performance paper masking tape for precise and flat paint edges

tesa® 4334 Precision Mask® consists of an extra-thin and strong paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 5 months after application, with 4 weeks of UV resistance. This enables multiple working processes in only one covering process.

Main Application

This tape is suited for almost all indoor paint works.

tesa® 4334 Precision Mask is applicable with water-based paints and lacquers. It even works with high-class spatula techniques. It is suitable for a variety of common surfaces such as glass, aluminium, hard-PVC and wood.

It is perfect for indoor applications when a precise razor-sharp paint edge is needed.

Technical Data

▪ Backing material	flat paper	▪ Elongation at break	4 %
▪ Total thickness	90 µm	▪ Tensile strength	30 N/cm
	3.5 mils		17.1 lbs/in
▪ Type of adhesive	acrylic	▪ UV-resistance	8 weeks
▪ Adhesion to steel	1.85 N/cm		
	16.9 oz/in		

Properties

▪ Hand tearability	●●●●	▪ Paint anchorage	●●●●
▪ Suitable for sensitive surfaces	●●●	▪ Sharp color Edge	●●●●
▪ Suitable for rough surfaces	●●●	▪ Conformability	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low