



TBP Converting, Inc.  
Q300 Contact Adhesive PDS

## Q300 California Compliant Contact Adhesive

Fast Tack, Water-Resistant, California Compliant

# Q300 California Compliant Contact Adhesive

### Features

- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- Water-Resistant Bond
- Meets and Exceeds the SCAQMD Rule 1168

### Description

Quality Aerosols Q300 California Compliant Contact Adhesive is a high strength, high shear, fast tack adhesive. Q300 is specially formulated for making permanent or temporary bonds. It can be used on paper, cardboard, fabric, leather, foil, fiberglass to metal, wood and a variety of other substrates. Q300 has a water resistant bond.

### Applications

Q300 is used for the permanent or temporary bonding to metal, cloth, fiberglass, leather, foil and other substrates.

### Product Usage

Q300 Adhesive is designed as a two surface bonding application. All surfaces should be tested for compatibility. Surfaces need to be dry and free of oil and debris. Spray an even coat of adhesive to cover 85%-95% of the surfaces. Allow adhesive to dry 3-5 minutes until it becomes tacky. For porous surfaces it is recommended to apply a second coat after the first coat has become tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

### Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk and canister products should be kept off the floor.

## Product Specifications

<b>Color</b>	<b>Natural</b>
<b>Solids</b>	<b>26% +/- 2%</b>
<b>VOC Content</b>	<b>38.1%</b>
<b>VOC Compliant CARB/OTC</b>	<b>Yes</b>
<b>Bonding Range</b>	<b>3-60 minutes</b>
<b>Dry/Tack Time</b>	<b>3-5 minutes</b>
<b>Spray Pattern</b>	<b>Web</b>
<b>Sizes Offered</b>	<b>12 oz</b>
<b>Warranty Period</b>	<b>1 year from manufacture date</b>
<b>Recommended layout</b>	<b>2.5g/ft<sup>2</sup></b>