



TBP Converting, Inc.
Zialoc 680 Series

Description

The Zialoc 680 foam tape is a cost effective, double-coated mounting tape that combines excellent bond strength and durability in interior applications. Zialoc 680 is designed as a cost-effective, medium-duty general purpose mounting tape. The water-based acrylic adhesive forms a strong permanent bond to a wide variety of substrates. A cross-linked EVA:PE copolymer foam provides excellent mechanical strength for 1/32" and 1/16" tapes. A soft cross-linked PE foam is used in 1/8" and 1/4" tapes to provide better conformability to textured surfaces.

Product Specifications		
Parameter	Test Method	Specification
Density	ASTM D - 1667	1/32 5 lb/cu ft 1/16 3 lb/cu ft 1/8-1/14 2 lb/cu ft
Tack @ 72F	38 oz/in (A)	PSTC - 105
Peel Adhesion @72F on SS 15 min	75 oz/in (FT)	PSTC - 101
Product Construction		
Liner Thickness	3.0 mil	
Liner Basis Weight	55lb	
Adhesive Type	2 mil Aqueous Acrylic	

- Forms permanent bond suitable for medium-duty mounting applications
- Durable
- Resists yellowing and degradation upon exposure to UV light
- Resists moderate levels of dust and dirt contamination
- Not recommended for applications requiring high water resistance
- Not recommend for long-term, heavy-duty mounting

TBP CONVERTING, INC. OR ANY OF THEIR ASSOCIATED COMPANIES MAKE NO WARRANTIES OF ANY KIND AS TO THIS PRODUCT, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If you allege this product is defective, your exclusive remedy shall be, at TBP CONVERTING, INC. or any of their associated companies' option to replace or repair the product or refund the purchase price of the product. All product selection should be made after appropriate engineering consultation and review of technical specifications. See: Manufacturer's technical specification sheet for applicable warranty information and disclaimers.