

TBP Converting, Inc. Rebonded Rubber Shipping Pads PDS



Rebonded **Rubber** Shipping Pads

Description

High density rebonded rubber with an aggressive adhesive system creates the ideal product for packaging and crating of heavy-weight items.

Available in custom sizes and thicknesses, these affordable pads keep your materials safe and secure during shipment and handling.

About Rebonded Rubber:

Rebonded Rubber is formed from pieces of a high quality rubber, bonded securely with resin. It is highly resilient, will compress with little exertion, and recover to 90% of its original thickness. Rebonded Rubber will not absorb moisture, rot over time, and is comprised of 97% post industrial content. It is made is the USA.

Specifications met by **Rebonded Rubber:**

- ASTM D-1752 Type I
- AASHTO M 153-70, Type I
- HH-F-341-F, Type II, Class A

Product Specifications*	
Parameter	Test Method
Specification	ASTM D 1752 Type I
Specification	AASHTO M 153-70, Type I
Specification	HH-F-341-F, Type II – Class A
Density (Min)	Apx. 30 PCF (lbs/ft3)
Recovery (Min)	90%
Compression	50 psi – 1 500 psi
Weathering	No Disintegration
Extrusion	Less than 0.25"
Color	Black
Standard Thickness (in.)	1/4, 1/2, 3/4, 1



TBP CONVERTING 400 Thoms Drive, Suite 411 Phoenixville, PA 19460 Tel: 800-850-3338 www.tbpconverting.com

DISCLAIMER OF ALL WARRANTIES

CONDITIONS OF SALE AND WARRANTY INFORMATION. TB PHILLY, INC. AND TBP CONVERTING TOGETHER WITH ANY OF THEIR ASSOCIATED COMPANIES MAKE NO WARRANTIES OF ANY KIND AS TO THIS PRODUCT, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. USER DETERMINES SUITABILITY OF PRODUCT FOR INTENDED USE AND ASSUMES ALL RISK. If you allege this product is defective, your exclusive remedy shall be, at TB PHILLY, INC., TBP CONVERTING or any of their associated companies' option, to replace or repair the product or refund the purchase price of the product. All production selection should be made after appropriate engineering consultation and review of technical specifications. See: Manufacturer's technical specification sheet for applicable warranty information and disclaimers.

D9S14