



# Product Data Sheet

## Q10 CONTACT ADHESIVE

High Strength, High Shear, Fast Tack

Q10 Spray Grade Contact Adhesive Bulk

### Features

- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- No Ozone Depleting Substances
- Water-Resistant Bond

### Description

Quality Aerosols Q10 Spray Grade Contact Adhesive is a high strength, high shear and fast tack adhesive. It is specially formulated for making permanent bonds. Q10 can be used on wood, particle board, plywood, plastics laminate, and many other substrates. Q10 Adhesive is resistant to high temperatures and has a water resistant bond.

### Applications

Q10 is used for the permanent bonding of wood, particle board, plywood, plastic laminate and many other substrates.

### Product Usage

Q10 Adhesive is designed as a two surface bonding application. All surfaces should be tested for compatibility. Surfaces should be dry and clean of oil and debris. Spray, roll or brush an even coat of adhesive to cover 80%-100% of the surfaces. Allow solvents to dry 2-5 minutes until the adhesive becomes tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours.

### Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Bulk and canister products should be kept off the floor.

## Product Specifications

<b>Color</b>	<b>Natural or Red</b>
<b>Solids</b>	<b>17% +/- 2%</b>
<b>VOC g/L</b>	<b>584.7 g/L</b>
<b>VOC Compliant CARB/OTC</b>	<b>NO</b>
<b>Bonding Range</b>	<b>2-45 minutes</b>
<b>Dry/Tack Time</b>	<b>2-5 minutes</b>
<b>Application Method</b>	<b>Spray Grade</b>
<b>Sizes Offered</b>	<b>5 gallon, 55 gallon</b>
<b>Warranty Period</b>	<b>1 year from manufacture date</b>

**Note: all results are based on 2.5-3.5g dried glue/ft<sup>2</sup>**



**QUALITY  
AEROSOLS**