



Product Data Sheet

Q81 California Compliant

Extended Open Time - Contact Adhesive

Q81 California Compliant EOT Contact Adhesive

Features

- Extended Open Time
- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- Haps Free
- Water-Resistant Bond

Description

Quality Aerosols Q81 California Compliant Contact Adhesive is a high strength, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds but with an extended open time for greater bonding flexibility. Our Q81 Adhesive is best effective when both surfaces are coated. It can be used on all types of wood, most metals, all laminates and veneers and many other substrates. Q81 is a high solids adhesive with a quick tack time. It is also resistant to high temperatures and has a water resistant bond.

Applications

Used for the permanent bonding of wood, metal, laminates, veneers, plastics, cloth, fiberglass insulation and other substrates.

Product Usage

Q81 Adhesive is designed as a two surface bonding application. Spray an even coat of adhesive to cover 85% to 95% of the surfaces. Surfaces need to be dry and free of oil and debris. Allow solvents to dry 2 to 5 minutes until adhesive becomes tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours. All surfaces should be tested for compatibility.

Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Canister products should be kept off the floor.

Product Specifications

Color	Natural or Red
Solids	38.4% +/- 1 %
VOC g/l	28.3 g/l
VOC Compliant CARB/OTC	Yes
Bonding Range	30+ minutes
Dry/Tack Time	2 to 5 minutes
Spray Pattern	Web
Sizes Offered	27#, 135#, 270#
Warranty Period	1 Year from manufacture date
Square Feet Coverage	approx. 62 ft ² per pound @2.5g dried glue

Note: All results are based on 2.5g dried glue/ft²

Tip for Spraying

Spraying Systems 6501AB or 9501 AB



**QUALITY
AEROSOLS**