



# Product Data Sheet

## Q8121 California Compliant

Air Assist - Extended Open Time - Contact Adhesive

Q8121 California Compliant EOT Contact Adhesive

### Features

- Extended Open Time
- Fast Tack, Great for Multiple Substrates
- Quick Tack Formula
- Haps Free
- Water-Resistant Bond

### Description

Quality Aerosols Q8121 California Compliant Contact Adhesive is an air assisted, high strength, high shear and fast tack adhesive. Our adhesive is specially formulated for making permanent bonds but with an extended open time for greater bonding flexibility. Our Q8121 Adhesive is best effective when both surfaces are coated. It can be used on all types of wood, most metals, all laminates and veneers and many other substrates. Q8121 is a high solids adhesive with a quick tack time. It is also resistant to high temperatures and has a water resistant bond.

### Applications

Used for the permanent bonding of wood, metal, laminates, veneers, plastics, cloth, fiberglass insulation and other substrates.

### Product Usage

Q8121 Adhesive is designed as a two surface bonding application. Spray an even coat of adhesive to cover 85% to 95% of the surfaces. Surfaces need to be dry and free of oil and debris. Allow solvents to dry 2 to 5 minutes until adhesive becomes tacky. Put the coated surfaces together and apply pressure. Full adhesive strength will be reached in 24 hours. All surfaces should be tested for compatibility.

### Storage

Store in a cool, dry, and well ventilated area. Do not handle or store near open flame or other heat sources. We recommend storing at or above 65°F. Canister products should be kept off the floor.

## Product Specifications

<b>Color</b>	<b>Natural or Red</b>
<b>Solids</b>	<b>38.4% +/- 1 %</b>
<b>VOC g/l</b>	<b>24.88 g/l</b>
<b>VOC Compliant CARB/OTC</b>	<b>Yes</b>
<b>Bonding Range</b>	<b>30+ minutes</b>
<b>Dry/Tack Time</b>	<b>2 to 5 minutes</b>
<b>Spray Pattern</b>	<b>Web</b>
<b>Sizes Offered</b>	<b>27#, 135#, 270#</b>
<b>Warranty Period</b>	<b>1 Year from manufacture date</b>
<b>Square Feet Coverage</b>	<b>approx. 62 ft<sup>2</sup> per pound @2.5g dried glue</b>

**Note: All results are based on 2.5g dried glue/ft<sup>2</sup>**

**Tip for Spraying**

**Spraying Systems 6501AB or 9501 AB**



**QUALITY  
AEROSOLS**