

SURFACE PROTECTION TAPES

# SPV 9310 | SPV 9320 | SPV 9330

## General description

The SPV 9300 series are Surface Protection Tapes suitable to protect rough and textured surfaces during light mechanical processes, storage and transport. These products consist of a modified PE or special PO film coated with a pressure sensitive acrylic-based adhesive.

## Features

- High initial tack
- Very high adhesion level
- Good wetting behavior
- Good humidity resistance
- Stretch-resistant film
- Transparent film for substrate identification and inspection
- Recyclable film

## Application

SPV 9300 series protection films are designed to protect low-gloss and textured surfaces from scratches and contamination throughout the supply chain. The transparent film in combination with a pressure-sensitive acrylic adhesive with high adhesion and excellent tack, ensures a reliable performance on rough substrates. SPV 9310 and SPV 9320 use a high-modulus PE film to prevent stretching during lamination, with SPV 9320 offering higher adhesion for more demanding applications. For extremely matte and rough surfaces such as textured plastics, laminates, and coatings like PVDF, PUR, and polyester, SPV 9330 combines a special PO film with a very high-adhesion acrylic adhesive for optimal protection and high repulsion resistance.

## Properties

	SPV 9310	SPV 9320	SPV 9330	Test method
Film type	Modified PE film	Modified PE film	PO film	n/a
Adhesive type	Acrylic-based	Acrylic-based	Acrylic-based	n/a
Total thickness	70µm	70µm	60µm	EN 1942
Adhesion to BA steel	320 cN/20mm	430 cN/20mm	290 cN/20mm	EN 1939
Tensile strength MD*	25 N/20mm	25 N/20mm	20 N/20mm	EN 14410
Elongation MD*	250%	250%	400%	
Weatherability on BA steel**	25h	None	None	ISO 4892-2
Color	Clear transparent	Clear transparent	Clear transparent	n/a

CAUTION: The above are typical values and should not be used in writing specifications. Details from the test methods are described on the customer product specification.

\*MD = Machine Direction

\*\*The weatherability is measured on BA steel. Depending on the substrate the weatherability performance can be different.

## SURFACE PROTECTION TAPES

**Warranty**

The product is guaranteed to be free from defect in material and workmanship at the time of delivery and will be suitable for use for a period of 12 months thereafter, subject to the conditions set out herein.

**Availability**

Widths: 1000 mm, 1250 mm, 1500 mm

Lengths: 200 m and 500 m (SPV 9330 only 200 m)

Please contact us for specific dimensions.

**Storage conditions**

The product should be protected against direct sunlight and extremes in temperature and humidity. Recommended storage and transport conditions are between 15 °C and 30 °C and between 40% and 75% relative humidity. The product should be stored in its original packaging in a well-ventilated room to avoid deterioration, deformation and contamination. Once removed from its packaging, it should be protected against dust and other impurities. Do not over stack the product, as this may cause deformation.

**Lamination guidelines**

- The tape should be applied to clean and dry surface by automatic mechanical means.
- To avoid entrapped air-bubbles, excessive tension and shear, the customer should determine appropriate lamination conditions.
- The best lamination conditions are obtained at a temperature between 15 °C and 40 °C.

**Application guidelines**

- In general, these tapes are immediately usable for further processing after lamination.
- These tapes are not recommended to be used in heavy forming processes.
- These tapes cannot be used on stainless steel, neither on lacquers containing softeners (such as PVC lacquers).
- These tapes are not designed for prolonged outside exposure.
- Surface protection tapes are not meant for permanent protection, they should be removed at the end of the supply chain.

## SURFACE PROTECTION TAPES

**General conditions of use and precautions**

The properties of the product might be adversely affected by various elements such as composition, condition and surface of and impurities in or on the substrate, temperature and humidity during storage, the surrounding environment at and after application and time of exterior use. When the product is used in combination with another material or process, the user shall assure the compatibility of the product in such combination and whether this combination results in the expected performance. The same principle applies in the event of product use in extreme conditions or circumstances, whether at or after the moment of application, including extended exposure to sunlight or extreme temperatures and pressure.

**Packaging, transport and storage**

During transport and storage the product should always be protected against direct sunlight and extremes in temperature and humidity and contained in its original packaging. Once removed from its packaging, it should be promptly applied and remain shielded from direct sunlight and extreme temperature as well as protected against dust and other impurities.

**Liability**

Except for its willful misconduct, Nitto Belgium's liability shall be limited to a replacement, a reimbursement or an additional delivery of the product, and shall not exceed the purchase price of the products. In no event shall Nitto be liable in respect of any indirect or consequential damages, including loss of profits. The above limitations of liability shall equally apply if Nitto Belgium has assisted in any manner with the selection, treatment or application of the product. Nitto's liability is limited to the terms and conditions provided in the Product Specification and Nitto's General Terms and Conditions of Sale.

**Product information**

This datasheet provides a general description of the product properties and application scope.

Full technical details in connection with this product are presented in the customer product specification, which is available upon request.

The information reflected in this datasheet is subject to change and the product described herein may be modified or discontinued without notice.

**Nitto Belgium NV has obtained the following certificates**

- ISO 9001
- ISO 14001
- IATF 16949